

LIMBURG.NET IN NUMBERS

910k inhabitants in 43 municipalities

70 collection teams a day 213 000 ton in 9 fractions

40 recycling parks
270 000 ton in 29 fractions


THE OPTIMO SYSTEM

Before






PRINCIPLE




EFFICIENCY in collection speed data




KILOMETERS/YEAR




TON CO₂ /year



COST



Loss of bags?





MARKET CONSULTATION

Several brainstorm sessions with all major constructors on the European market, process guidance by PIO and Verhaert

Conclusive report:

"Optimalisation and innovation are feasible, and bear opportunities for the entire sector"

INNOVATION TENDER

LAUNCH R&D TENDER

- Information sessions for all constructors involved
- Explaining the set-up:
 - 2 phase: PoP and PoC
 - Multiple parties possible
- Determing evaluation criteria and commission (PIO, Limburg.net, Bionerga, university)

GENERAL OBJECTIVE

Higher load of intact bags

AND
No dependency
on operators!

Factors:

•	Maximal tearing percentage < 4%		(<2% including bag improvement)
•	Load	280 kg/m3	
•	Safety	compliance to norms/regulation	
•	Ergonomy	load height = 1 m	
•	Load speed	min ± 3 ton/h	
•	Dimensions	H < 3m85	
		L < 10m50	
		W < 2m55	

PHASED APPROACH

january 19

end-10

and 20

Conceive solutions

"proof of principle"

Develop, simulate, compare, experiment...

2 parties: VDK and VDL

Prototyping & validation

"proof of concept"

 Building prototypes
 Validate in the everyday practice with Limburg.net

2 parties: VDK and VDL

SET-UP: PRE-COMMERCIAL PURCHASE



Flanders Max 250k



Limburg.net
Max 250k





Constructors 150k each

VDL SIDE LOADER

Conceptual

- Good results in stationary compaction block test
- Top loading: better than grabbing the waste with standard rear loader?
- Possibility to change containers



Criteria

Intact bags

Only reasonable results below 4 tons

Load volume

- Possible efficiency gain by interchangeable containers
- But mitigated by tearing of bags over 4 tons loading weight

Cost

- + 50% extra capital investment
- Higher operational costs?

Load speed

About 20% slower

VDL SIDE LOADER

Conceptual

- How to avoid cutting the bags with compaction plate by operators?
- More sensoring and setting up of fail-safes
- · Enable compaction cycles while driving
- Enable automated compaction cycles with 3D fill grade cameras



Criteria

Intact bags

- Good results, comparable to reference
- Possible improvements on the table

Load volume


• $25m^3 \rightarrow 28m^3$

Cost

- Comparable to standard truck
- Efficiency gains by loading speed

Load speed

Significantly faster than reference



EVALUATION

- Side loader
 - "sufficient", but no further action

Read loader

- "sufficient", but possibly successful after new iterations on sensoring
- 3D-camera and light screen (to enable compaction cycles while moving) technological innovations for the entire waste sector

"Unsufficient"

"Sufficient"

"Succesful"





SET-UP: INTELLECTUAL PROPERTY

- 1. No obligation to purchase a certain amount
- 2. Intellectual property for involved constructors, but "right of use" on new knowledge
- 3. Constructor has to market the technology at a fair price, if not there is cause for a "call-back" of this technology

COMMUNICATION ON THE RESULTS OF THE PROJECT

Information sessions in 2021:

- For the constructor market: preceding the tendering of Optimo collection trucks
- Private collection companies: preceding the tendering of Optimo collection contracts

"High level" information, no technical details

TENDER FOR TRUCKS

LIMBURG.NET DA'S PROPER GEDAAN

Limburg.net

New fleet:

- 16 rear loader (3 axles, 28m³)
- 1 rear loader (2 axles, 21m³)

ITERATIONS

VDK

- sensor on load edge (fail-safe)
- software update
- New IR-camera

Terberg

- tests with "HCT"
- suggestions



PARTICIPANTS

- VDK Mol cy
- Terberg Rosroca
- Geesink Norba

RESULT

Limburg.net

- 9x VDK Optimo truck
- 8x Terberg Optimo truck

1x BEV Optimo truck currently in tender (2024)

PRIVATE COLLECTORS

Renewi:

25x VDK Optimo truck

Veolia:

2x VDK Optimo truck

Inroads to monostream collection:

- 28m³ for plastics collection
- Light screen (collection speed ↑ ↑)